

**DAMAVAND POWER PLANT (DPGM)****لیست لوازم مصرفی در بخش ابزار دقیق - پیوست شماره ۳**

ROW	DESCRIPTION	QUANTITY REQUIRED	PRICE (RIAL)
1	RTD (TEMP TRANSMITTER) DC-10~36V 4/20MA T:-40~85C L:700MM 3WIRE SINGLE/WHITE/RED MANU:WIKI	3	
2	TEMP GAUGE 0-100C CONNECTION:1/2, NPT PROB LENGHT:100mm Ordering Bimetal Thermometer:31040d105g4.man:wika	1	
3	TEMP. GAUGE WIKI 1-100°C Con:1/2 Female prob len:150mm prob dia:7mm Acc:1°C Face:10Cm	1	
4	THERMOCOUPLE K-CLASS:0.75-MANU:WISE-Element length1737 L PROB:1500 range 0~780c- 1 1/4"NPT-output 4~20ma	3	
5	THERMOCOUPLE-CLASS 0.4-K TYPE TC-(0-830c) 4-20mA AI-WISE+ABB-R162+TH02 (قطر و طول) 5mm, 5m	1	
6	STEAM TURBINE BEARING THERMOCOUPLE - Heraeus - 24 VDC - 0~150 °C- B300*7000-3K NICR- NI PM0A61E37H45-01-0010-L- KUN672.20	3	
7	THERMOCOUPLE TYPE:T Q SENSOR: 4.8 mm L SENSOR: 14 cm MANU: wise TEMP RENGE:0-230C	2	
8	TEMPRATURE TRANSMITTER (RTD)10~36VDC 4-20mA TEMP:-40+85°C L:320MM MANU:WIKI	3	
9	Temp. Gauge, Manu:WISE, Model No.:T2104B1ED3109S1, STEM LENGTHH: 13Cm	2	
10	CWP BEARING TEMP.GERFAN.PT100SINGLE ELEMENT.CLASS A.100ohm in0c.1/8"GAS style.3wires.AISI316.Insulatorceramic	3	
11	THERMOCOUPLE TYPE:2K MAT:SS316.0-+670C NiCr/Ni FOR V94.2 EXHAUST.MAN:ABB	10	
12	Head mounted Temperature Transmitter TH02.MANU: ABB.24VDC.output:4- 20ma.IP65.Accuracy:0.3%full Scale	10	
13	THERMOCOUPLE CLASS:0.75 ELEMENT:T MANU:WISE PROB LENGTH:16.5Cm PROB DIAMETER: 7mm	1	
14	THERMOCOUPLE TYPE:K MANU:WISE ELEMENT LENGTH 30CM PROB:2500MM RANGE:0~640 npt-out put 4~20ma1/2inch	1	
TOTAL PRICE (RIAL)			